



# Ceramic Spray Wax

## Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010  
Issue date: 5/20/2024 Revision date: 5/20/2026 Version: 1.0

### SECTION 1: Identification

#### 1.1. Product identifier

Product form : Mixture  
Trade name : Ceramic Spray Wax  
Type of product : Detergent  
Product code : SH1703  
Product group : Trade product

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture :  
Use of the substance/mixture : Cleaning/washing agents and additives

#### 1.3. Supplier's details

##### Distributor

Shield Chemicals (Pty) Ltd  
9 London Rd Apex  
P.O. Box 1939  
1501 Benoni – Gauteng  
South Africa  
T (011) 421 7111  
Contact: Jayson Clark

#### 1.4. Emergency telephone number

Emergency number : (011) 421 7111

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to the United Nations GHS

Flammable liquids, Category 2	H225
Skin corrosion/irritation, Category 3	H316
Serious eye damage/eye irritation, Category 2A	H319

Full text of H-statements: see section 16

#### 2.2. Label elements

##### Labelling according to the United Nations GHS

Hazard pictograms (GHS ZA) :



Signal word (GHS-ZA) :

Danger

Hazard statements (GHS ZA) :

H225 - Highly flammable liquid and vapour  
H316 - Causes mild skin irritation  
H319 - Causes serious eye irritation

Precautionary statements (GHS ZA) :

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 - Keep container tightly closed.  
P240 - Ground and bond container and receiving equipment.  
P241 - Use explosion-proof equipment.  
P242 - Use non-sparking tools.  
P243 - Take action to prevent static discharges.  
P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/....

# Ceramic Spray Wax

## Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse affected areas with water [or shower].

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P332+P317 - If skin irritation occurs: Get medical help.

P370+P378 - In case of fire: Use ... to extinguish.

P403+P235 - Store in a well-ventilated place. Keep cool.

P501 - Dispose of contents/container to ....

### 2.3. Other hazards

Adverse physicochemical, human health and environmental effects : Harmful to aquatic life

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to the United Nations GHS
2-Butoxyethanol	-	8.75	Flam. Liq. Not classified Acute Tox. 4 (Oral), H302 Acute Tox. Not classified (Dermal) Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Aquatic Acute Not classified
2-propanol	CAS-No.: 67-63-0	8.75	Flam. Liq. 2, H225 Acute Tox. Not classified (Oral) Acute Tox. Not classified (Dermal) Eye Irrit. 2A, H319 STOT SE 3, H336 Asp. Tox. Not classified Aquatic Acute Not classified
1,2-propanediol	CAS-No.: 57-55-6	1	Flam. Liq. Not classified Acute Tox. Not classified (Oral) Acute Tox. 5 (Dermal), H313 Aquatic Acute Not classified

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.  
First-aid measures after skin contact : Wash skin with plenty of water.  
First-aid measures after eye contact : Rinse eyes with water as a precaution.  
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

No additional information available

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

# Ceramic Spray Wax

## Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

#### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

#### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

No additional information available

##### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area.

##### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.  
Methods for cleaning up : Take up liquid spill into absorbent material.  
Other information : Dispose of materials or solid residues at an authorized site.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment.  
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### 2-propanol (67-63-0)

##### South Africa - Occupational Exposure Limits (Airborne Pollutants)

Local name	Isopropyl alcohol (Propan-2-ol)
OEL TWA	980 mg/m <sup>3</sup>
OEL TWA	400 ppm
OEL STEL	1225 mg/m <sup>3</sup>

# Ceramic Spray Wax

## Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

<b>2-propanol (67-63-0)</b>	
OEL STEL	500 ppm
Regulatory reference	Government Notice No. R 904
<b>1,2-propanediol (57-55-6)</b>	
<b>South Africa - Occupational Exposure Limits (Airborne Pollutants)</b>	
Local name	Propylene glycol (Propane-1,2-diol)
OEL TWA	470 mg/m <sup>3</sup> total (particulate & vapor) 10 mg/m <sup>3</sup> particulate
OEL TWA	150 ppm total (particulate & vapor)
Regulatory reference	Government Notice No. R 904

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.  
Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures, such as personal protective equipment (PPE)

Hand protection : Protective gloves  
Eye protection : Safety glasses  
Skin and body protection : Wear suitable protective clothing  
Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment

#### Personal protective equipment symbol(s):



### 8.4. Exposure limit values for the other components

No additional information available

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid  
Appearance : Liquid.  
Colour : No data available  
Odour : No data available  
Odour threshold : No data available  
pH : 9 – 9.3  
pH solution : No data available  
Relative evaporation rate (butylacetate=1) : No data available  
Relative evaporation rate (ether=1) : No data available  
Melting point : Not applicable  
Freezing point : No data available  
Boiling point : No data available  
Flash point : No data available  
Auto-ignition temperature : No data available  
Decomposition temperature : No data available  
Flammability : Not applicable  
Vapour pressure : No data available  
Vapour pressure at 50°C : No data available  
Relative vapour density at 20°C : No data available  
Relative density : No data available  
Relative density of saturated gas/air mixture : No data available

# Ceramic Spray Wax

## Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

Density	: No data available
Relative gas density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Partition coefficient n-octanol/water (Log Kow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: 1500 – 3000 mPa·s
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available
Lower explosion limit	: No data available
Upper explosion limit	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

2-Butoxyethanol	
LD50 oral rat	≈ 470 mg/kg
LD50 dermal rabbit	≈ 220 mg/kg
2-propanol (67-63-0)	
LD50 oral rat	5840 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	16400 mg/kg bodyweight (Equivalent or similar to OECD 402, 24 h, Rabbit, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat [ppm]	> 10000 ppm (Equivalent or similar to OECD 403, 6 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))

# Ceramic Spray Wax

## Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

<b>1,2-propanediol (57-55-6)</b>	
LD50 oral rat	22000 mg/kg (Rat, Experimental value, Oral)
LD50 dermal rabbit	> 2000 mg/kg bodyweight (24 h, Rabbit, Experimental value, Dermal, 14 day(s))
Skin corrosion/irritation	: Causes mild skin irritation. pH: 9 – 9.3
Serious eye damage/irritation	: Causes serious eye irritation. pH: 9 – 9.3
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
<b>2-propanol (67-63-0)</b>	
STOT-single exposure	Not available
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
<b>2-Butoxyethanol</b>	
Animal studies and expert judgment for classification	False
<b>2-propanol (67-63-0)</b>	
Animal studies and expert judgment for classification	False
<b>1,2-propanediol (57-55-6)</b>	
Animal studies and expert judgment for classification	False

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: Harmful to aquatic life.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

<b>2-Butoxyethanol</b>	
LC50 - Fish [1]	≈ 2000 g/l
<b>2-propanol (67-63-0)</b>	
LC50 - Fish [1]	9640 – 10000 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Lethal)
Partition coefficient n-octanol/water (Log Pow)	0.05 (Weight of evidence approach, 25 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.185 – 0.541 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
<b>1,2-propanediol (57-55-6)</b>	
LC50 - Fish [1]	51600 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Experimental value)
LC50 - Fish [2]	40613 mg/l (Other, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value)
ErC50 algae	24200 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
BCF - Other aquatic organisms [1]	0.09

# Ceramic Spray Wax

## Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

1,2-propanediol (57-55-6)	
Partition coefficient n-octanol/water (Log Pow)	-1.07 (Experimental value, EU Method A.8: Partition Coefficient, 20.5 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.46 (log Koc, Calculated value)

### 12.2. Persistence and degradability

Ceramic Spray Wax	
Persistence and degradability	No additional information available

2-propanol (67-63-0)	
Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.19 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.23 g O <sub>2</sub> /g substance
ThOD	2.4 g O <sub>2</sub> /g substance

1,2-propanediol (57-55-6)	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.96 – 1.08 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	1.63 g O <sub>2</sub> /g substance
ThOD	1.69 g O <sub>2</sub> /g substance

### 12.3. Bioaccumulative potential

Ceramic Spray Wax	
Bioaccumulative potential	No additional information available

2-propanol (67-63-0)	
Partition coefficient n-octanol/water (Log Pow)	0.05 (Weight of evidence approach, 25 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.185 – 0.541 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

1,2-propanediol (57-55-6)	
BCF - Other aquatic organisms [1]	0.09
Partition coefficient n-octanol/water (Log Pow)	-1.07 (Experimental value, EU Method A.8: Partition Coefficient, 20.5 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.46 (log Koc, Calculated value)
Bioaccumulative potential	Not bioaccumulative.

### 12.4. Mobility in soil

Ceramic Spray Wax	
Mobility in soil	No additional information available

2-propanol (67-63-0)	
Surface tension	0.021 N/m (25 °C)
Partition coefficient n-octanol/water (Log Pow)	0.05 (Weight of evidence approach, 25 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.185 – 0.541 (log Koc, SRC PCKOCWIN v2.0, Calculated value)

# Ceramic Spray Wax

## Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

<b>2-propanol (67-63-0)</b>	
Ecology - soil	Highly mobile in soil.
<b>1,2-propanediol (57-55-6)</b>	
Surface tension	71.6 mN/m (21.5 °C, 1.01 g/l, EU Method A.5: Surface tension)
Partition coefficient n-octanol/water (Log Pow)	-1.07 (Experimental value, EU Method A.8: Partition Coefficient, 20.5 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.46 (log Koc, Calculated value)
Ecology - soil	Highly mobile in soil.

### 12.5. Other adverse effects

Ozone : Not classified  
Other adverse effects : No additional information available

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

## SECTION 14: Transport information

In accordance with SANS / IMDG / IATA

SANS	IMDG	IATA
<b>14.1. UN number</b>		
Not regulated for transport		
<b>14.2. Proper Shipping Name</b>		
Not applicable	Not applicable	Not applicable
<b>14.3. Transport hazard class(es)</b>		
Not applicable	Not applicable	Not applicable
Not applicable	Not applicable	Not applicable
<b>14.4. Packing group</b>		
Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>		
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No
No supplementary information available		

### 14.6. Special precautions for user

#### SANS

No data available

#### IMDG

No data available

#### IATA

No data available

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable



# Ceramic Spray Wax

## Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

### SECTION 15: Regulatory information

#### 15.1. Safety, health, and environmental national regulations specific for the product

No additional information available

### SECTION 16: Other information

Issue date : 20/05/2024

Revision date : 20/05/2026

#### Full text of H-statements

H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H227	Combustible liquid
H301	Toxic if swallowed
H302	Harmful if swallowed
H303	May be harmful if swallowed
H311	Toxic in contact with skin
H313	May be harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H316	Causes mild skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H330	Fatal if inhaled
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H413	May cause long lasting harmful effects to aquatic life

Safety Data Sheet (SDS), South Africa

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.