



# Ceramic Vinyl, Plastic & Rubber Dressing

## Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010  
Issue date: 8/19/2024 Revision date: 8/19/2026

### SECTION 1: Identification

#### 1.1. Product identifier

Product form : Mixture  
Trade name : Ceramic Vinyl, Plastic & Rubber Dressing  
Product code : SH1700

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture :

#### 1.3. Supplier's details

Shield Chemicals (Pty) Ltd  
9 London Rd Apex  
P.O. Box 1939  
1501 Benoni – Gauteng  
South Africa  
T (011) 421 7111  
Contact: Jayson Clark

#### 1.4. Emergency telephone number

Emergency number : (011) 421 7111

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to the United Nations GHS

Flammable liquids, Category 2 H225  
Serious eye damage/eye irritation, Category 2A H319  
Full text of H-statements: see section 16

#### 2.2. Label elements

##### Labelling according to the United Nations GHS

Hazard pictograms (GHS ZA) :



Signal word (GHS-ZA) :

Danger

Hazard statements (GHS ZA) :

H225 - Highly flammable liquid and vapour  
H319 - Causes serious eye irritation

Precautionary statements (GHS ZA) :

P233 - Keep container tightly closed.  
P240 - Ground and bond container and receiving equipment.  
P241 - Use explosion-proof electrical equipment.  
P242 - Use non-sparking tools.  
P243 - Take action to prevent static discharges.  
P280 - Wear protective clothing, eye protection, face protection.  
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse affected areas with water [or shower].  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P370+P378 - In case of fire: Use foam to extinguish.  
P403+P235 - Store in a well-ventilated place. Keep cool.  
P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

# Ceramic Vinyl, Plastic & Rubber Dressing

## Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to the United Nations GHS
2-propanol	CAS-No.: 67-63-0	10	Flam. Liq. 2, H225 Acute Tox. Not classified (Oral) Acute Tox. Not classified (Dermal) Eye Irrit. 2A, H319 STOT SE 3, H336 Asp. Tox. Not classified Aquatic Acute Not classified

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general : If you feel unwell, seek medical advice.  
First-aid measures after eye contact : Rinse immediately with plenty of water for 15 minutes.  
First-aid measures after ingestion : Do not induce vomiting because of corrosive effects.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Causes eye irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Class A foam extinguisher.  
Unsuitable extinguishing media : Foam.

### 5.2. Special hazards arising from the substance or mixture

No additional information available

### 5.3. Advice for firefighters

No additional information available

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

No additional information available

#### 6.1.1. For non-emergency personnel

No additional information available

# Ceramic Vinyl, Plastic & Rubber Dressing

## Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

### 6.1.2. For emergency responders

No additional information available

### 6.2. Environmental precautions

No additional information available

### 6.3. Methods and material for containment and cleaning up

No additional information available

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

No additional information available

### 7.2. Conditions for safe storage, including any incompatibilities

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 2-propanol (67-63-0)

#### South Africa - Occupational Exposure Limits (Airborne Pollutants)

Local name	Isopropyl alcohol (Propan-2-ol)
OEL TWA	980 mg/m <sup>3</sup>
OEL TWA	400 ppm
OEL STEL	1225 mg/m <sup>3</sup>
OEL STEL	500 ppm
Regulatory reference	Government Notice No. R 904

### 8.2. Appropriate engineering controls

No additional information available

### 8.3. Individual protection measures, such as personal protective equipment (PPE)

No additional information available

### 8.4. Exposure limit values for the other components

No additional information available

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: No data available
Colour	: White.
Odour	: No data available
Odour threshold	: No data available
pH	: No data available
pH solution	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available

# Ceramic Vinyl, Plastic & Rubber Dressing

## Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability	: No data available
Vapour pressure	: No data available
Vapour pressure at 50°C	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: No data available
Relative density of saturated gas/air mixture	: No data available
Density	: No data available
Relative gas density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Partition coefficient n-octanol/water (Log Kow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available
Lower explosion limit	: No data available
Upper explosion limit	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

No additional information available

### 10.3. Possibility of hazardous reactions

No additional information available

### 10.4. Conditions to avoid

No additional information available

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

No additional information available

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

# Ceramic Vinyl, Plastic & Rubber Dressing

## Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

2-propanol (67-63-0)	
LD50 oral rat	5840 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	16400 mg/kg bodyweight (Equivalent or similar to OECD 402, 24 h, Rabbit, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat [ppm]	> 10000 ppm (Equivalent or similar to OECD 403, 6 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified

2-propanol (67-63-0)	
STOT-single exposure	Not available
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

2-propanol (67-63-0)	
Animal studies and expert judgment for classification	False

## SECTION 12: Ecological information

### 12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

2-propanol (67-63-0)	
LC50 - Fish [1]	9640 – 10000 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Lethal)
Partition coefficient n-octanol/water (Log Pow)	0.05 (Weight of evidence approach, 25 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.185 – 0.541 (log Koc, SRC PCKOCWIN v2.0, Calculated value)

### 12.2. Persistence and degradability

Ceramic Vinyl, Plastic & Rubber Dressing	
Persistence and degradability	No additional information available
2-propanol (67-63-0)	
Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.19 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.23 g O <sub>2</sub> /g substance
ThOD	2.4 g O <sub>2</sub> /g substance

# Ceramic Vinyl, Plastic & Rubber Dressing

## Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

### 12.3. Bioaccumulative potential

Ceramic Vinyl, Plastic & Rubber Dressing	
Bioaccumulative potential	No additional information available
2-propanol (67-63-0)	
Partition coefficient n-octanol/water (Log Pow)	0.05 (Weight of evidence approach, 25 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.185 – 0.541 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

### 12.4. Mobility in soil

Ceramic Vinyl, Plastic & Rubber Dressing	
Mobility in soil	No additional information available
2-propanol (67-63-0)	
Surface tension	0.021 N/m (25 °C)
Partition coefficient n-octanol/water (Log Pow)	0.05 (Weight of evidence approach, 25 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.185 – 0.541 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.

### 12.5. Other adverse effects

Ozone : Not classified  
Other adverse effects : No additional information available

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

No additional information available

## SECTION 14: Transport information

In accordance with SANS / IMDG / IATA

SANS	IMDG	IATA
14.1. UN number		
Not regulated for transport		
14.2. Proper Shipping Name		
Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)		
Not applicable	Not applicable	Not applicable
Not applicable	Not applicable	Not applicable
14.4. Packing group		
Not applicable	Not applicable	Not applicable
14.5. Environmental hazards		
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No

# Ceramic Vinyl, Plastic & Rubber Dressing

## Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

SANS	IMDG	IATA
No supplementary information available		

### 14.6. Special precautions for user

#### SANS

No data available

#### IMDG

No data available

#### IATA

No data available

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health, and environmental national regulations specific for the product

No additional information available

## SECTION 16: Other information

Issue date : 19/08/2024  
Revision date : 19/08/2026

Full text of H-statements	
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H301	Toxic if swallowed
H302	Harmful if swallowed
H303	May be harmful if swallowed
H311	Toxic in contact with skin
H313	May be harmful in contact with skin
H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H330	Fatal if inhaled
H336	May cause drowsiness or dizziness
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H413	May cause long lasting harmful effects to aquatic life

Safety Data Sheet (SDS), South Africa

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.