

#### Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010 Issue date: 5/6/2024 Revision date: 5/6/2026 Version: 1.1

### **SECTION 1: Identification**

#### **1.1. Product identifier**

Product form Trade name Type of product Product code Product group

: Mixture : Miraplate liquid

- : Polishing agent
- SH44, SH297, SH09, SH21, SH08 :
- Trade product ÷

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

:

Use of the substance/mixture

#### 1.3. Supplier's details

#### Manufacturer

Shield Chemicals (Pty) Ltd 9 London Rd Apex P.O. Box 1939 1501 Benoni - Gauteng South Africa T (011) 421 7111 Contact: Jayson Clark

#### 1.4. Emergency telephone number

Emergency number

: (011) 421 7111

SECTION 2: Hazards identification		
2.1. Classification of the substance or mixture		
Classification according to the United Nations GHS		
Flammable liquids, Category 3	H226	
Skin corrosion/irritation Not classified		
Germ cell mutagenicity, Category 1B	H340	
Carcinogenicity, Category 1B	H350	
Specific target organ toxicity – Repeated exposure, Category 2 H373		
Hazardous to the aquatic environment – Acute Hazard Not classifier	t	
Hazardous to the aquatic environment – Chronic Hazard Not classified		
Full text of H-statements: see section 16		
2.2. Label elements		

#### Labelling according to the United Nations GHS


Hazard pictograms (GHS ZA)

:		
:	Danger	

Signal word (GHS-ZA) Hazardous ingredients

Hazard statements (GHS ZA)

Precautionary statements (GHS ZA)



- H340 May cause genetic defects
- H350 May cause cancer
- H373 May cause damage to organs through prolonged or repeated exposure
- : P203 Obtain, read and follow all safety instructions before use.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

## Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

	<ul> <li>P233 - Keep container tightly closed.</li> <li>P240 - Ground and bond container and receiving equipment.</li> <li>P241 - Use explosion-proof equipment.</li> <li>P242 - Use non-sparking tools.</li> <li>P243 - Take action to prevent static discharges.</li> <li>P260 - Do not breathe dusts or mists.</li> <li>P280 - Wear eye protection, protective clothing, protective gloves.</li> <li>IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse affected areas with water [or shower].</li> <li>P318 - IF exposed or concerned, get medical advice.</li> <li>P319 - Get medical help if you feel unwell.</li> <li>P370+P378 - In case of fire: Use sand, foam, carbon dioxide (CO2), dry extinguishing powder to extinguish.</li> <li>P403+P235 - Store in a well-ventilated place. Keep cool.</li> <li>P405 - Store locked up.</li> <li>P501 - Dispose of contents and container to a hazardous or special waste collection point.</li> </ul>
2.3. Other hazards	
Adverse physicochemical, human health and environmental effects	: Flammable liquid and vapour,May cause cancer,May cause genetic defects,May cause damage to organs through prolonged or repeated exposure,Causes mild skin irritation,Toxic to aquatic life,Harmful to aquatic life with long lasting effects.

### SECTION 3: Composition/information on ingredients

### 3.1. Substances

#### Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to the United Nations GHS
nonane	CAS-No.: 111-84-2	6.0 - 12.0	Flam. Liq. 3, H226 Acute Tox. Not classified (Oral) Acute Tox. 5 (Dermal), H313 STOT RE 2, H373 Aquatic Acute 1, H400
Decane	CAS-No.: 124-18-5	6.0 - 12.0	Flam. Liq. 3, H226 Acute Tox. 5 (Dermal), H313
Undecane	CAS-No.: 1120-21-4	2.0 -8.0	Flam. Liq. 4, H227 Acute Tox. 5 (Dermal), H313
Naphtha (petroleum), hydrodesulfurized heavy / Naphtha (petroleum), hydrodesulfurized heavy	CAS-No.: 64742-82-1	1.0 - 3.0	Flam. Liq. 2, H225 Acute Tox. Not classified (Oral) Muta. 1B, H340 Carc. 1B, H350 STOT RE 1, H372 Asp. Tox. 1, H304
Kerosine (petroleum)	CAS-No.: 8008-20-6	0.1 - 1.0	Flam. Liq. 3, H226 Acute Tox. Not classified (Oral) Acute Tox. 5 (Dermal), H313 STOT RE Not classified Asp. Tox. 1, H304

## Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

Name	Product identifier	%	Classification according to the United Nations GHS
heptane	CAS-No.: 142-82-5	0.2 - 0.9	Flam. Liq. 2, H225 Acute Tox. Not classified (Oral) Acute Tox. 5 (Dermal), H313 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
methylcyclohexane	CAS-No.: 108-87-2	0.2 - 0.9	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
octane	CAS-No.: 111-65-9	0.1 - 0.5	Flam. Liq. 2, H225 Acute Tox. Not classified (Oral) Acute Tox. 5 (Dermal), H313 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
toluene	CAS-No.: 108-88-3	0.01 - 0.09	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304
xylene	CAS-No.: 1330-20-7	0.01 - 0.09	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315

#### SECTION 4: First aid measures

4.1. Description of first aid measures	
First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.
4.2. Most important symptoms and effects, both acute and delayed	

Symptoms/effects after skin contact

: Irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures	
5.1. Extinguishing media	
Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.

### Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

5.2. Special hazards arising from the substance or mixture		
Fire hazard Hazardous decomposition products in case of fire	<ul><li>Flammable liquid and vapour.</li><li>Toxic fumes may be released.</li></ul>	
5.3. Advice for firefighters		
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.	

SECTION 6: Accidental release measures		
6.1. Personal precautions, protective	equipment and emergency procedures	
No additional information available		
6.1.1. For non-emergency personnel		
Emergency procedures	: No open flames, no sparks, and no smoking. Only qualified personnel equipped with suitable protective equipment may intervene. Do not breathe vapours.	
6.1.2. For emergency responders		
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".	
6.2. Environmental precautions		

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up		
For containment	: Collect spillage.	
Methods for cleaning up	<ul> <li>Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.</li> </ul>	
Other information	: Dispose of materials or solid residues at an authorized site.	

SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Precautions for safe handling	: Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Do not breathe vapours. Avoid contact with skin and eyes.
Hygiene measures	: Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
7.2. Conditions for safe storage, including	g any incompatibilities
Technical measures Storage conditions	<ul><li>Ground/bond container and receiving equipment.</li><li>Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.</li></ul>

#### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

## Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

-	
methylcyclohexane (108-87-2)	
South Africa - Occupational Exposure Limits (Air	borne Pollutants)
Local name	Methylcyclohexane
OEL TWA	1600 mg/m <sup>3</sup>
OEL TWA	400 ppm
OEL STEL	2000 mg/m <sup>3</sup>
OEL STEL	500 ppm
Regulatory reference	Government Notice No. R 904
toluene (108-88-3)	
South Africa - Occupational Exposure Limits (Air	borne Pollutants)
Local name	Toluene
OEL TWA	188 mg/m <sup>3</sup>
OEL TWA	50 ppm
OEL STEL	560 mg/m <sup>3</sup>
OEL STEL	150 ppm
Remark	Sk (Danger of cutaneous absorption)
Regulatory reference	Government Notice No. R 904
xylene (1330-20-7)	· · · · · · · · · · · · · · · · · · ·
South Africa - Occupational Exposure Limits (Air	borne Pollutants)
Local name	Xylene, o-, m-, p- or mixed isomers
OEL TWA	218 mg/m <sup>3</sup>
OEL TWA	50 ppm
OEL STEL	435 mg/m <sup>3</sup>
OEL STEL	100 ppm
Remark	Sk (Danger of cutaneous absorption)
Regulatory reference	Government Notice No. R 904
8.2. Appropriate engineering controls	
Appropriate engineering controls Environmental exposure controls	<ul><li>Ensure good ventilation of the work station.</li><li>Avoid release to the environment.</li></ul>
8.3. Individual protection measures, such as	personal protective equipment (PPE)
Hand protection	: Protective gloves
Eye protection	: Safety glasses
Skin and body protection	: Wear suitable protective clothing
Respiratory protection Personal protective equipment symbol(s):	: [In case of inadequate ventilation] wear respiratory protection.
8.4 Exposure limit values for the other com	nononte

#### 8.4. Exposure limit values for the other components

No additional information available

### Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

	and the second
9.1. Information on basic physical and ch	iemical properties
Physical state	: Liquid
Appearance	: Viscous liquid.
Colour	: light brown.
Odour	: No data available
Odour threshold	: No data available
рН	: 8.5 – 9.5
pH solution	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: ≈45 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability	: Not applicable
Vapour pressure	: No data available
Vapour pressure at 50°C	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: No data available
Relative density of saturated gas/air mixture	: No data available
Density	: No data available
Relative gas density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Partition coefficient n-octanol/water (Log Kow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: 3600 – 4600 mPa·s
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available
Lower explosion limit	: No data available

: No data available

#### 9.2. Other information

Upper explosion limit

No additional information available

#### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Flammable liquid and vapour.

#### **10.2. Chemical stability**

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

## Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11.1. Information on toxicological e	ffects	
Acute toxicity (oral) Acute toxicity (dermal) Acute toxicity (inhalation)	<ul> <li>Not classified</li> <li>Not classified</li> <li>Not classified</li> </ul>	
nonane (111-84-2)		
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), Guideline: EPA OPPTS 870.1100 (Acute Oral Toxicity)	
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EPA OPPTS 870.1200 (Acute Dermal Toxicity)	
LC50 Inhalation - Rat	17 mg/l air Animal: rat, Animal sex: male, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), 95% CL: 14 - 21	
Undecane (1120-21-4)		
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)	
LD50 dermal rabbit	≥ 3160 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)	
Decane (124-18-5)		
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)	
LD50 dermal rabbit	≥ 3160 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)	
Naphtha (petroleum), hydrodesulfu	rized heavy / Naphtha (petroleum), hydrodesulfurized heavy (64742-82-1)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)	
Kerosine (petroleum) (8008-20-6)		
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.1175 (Acute Oral Toxicity), Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)	
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: EPA OTS 798.1100 (Acute Dermal Toxicity), Guideline: OECD Guideline 402 (Acute Dermal Toxicity)	
LC50 Inhalation - Rat	<ul> <li>&gt; 5.28 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity),</li> <li>95% CL: 0,42 -</li> </ul>	
heptane (142-82-5)		
LD50 oral rat	> 5000 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Male / female, Read- across, Oral)	
LD50 dermal rabbit	> 2000 mg/kg bodyweight (Equivalent or similar to OECD 402, 24 h, Rabbit, Male / female, Read-across, Dermal)	
LC50 Inhalation - Rat	> 29.29 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimenta value, Inhalation (vapours))	
octane (111-65-9)		
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), Guideline: EPA OPPTS 870.1100 (Acute Oral Toxicity)	

### Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

#### octane (111-65-9) LD50 dermal rabbit > 2000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EPA OPPTS 870.1200 (Acute Dermal Toxicity) LC50 Inhalation - Rat > 24.88 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity) Skin corrosion/irritation : Not classified. pH: 8.5 – 9.5 Serious eye damage/irritation Not classified pH: 8.5 - 9.5 Respiratory or skin sensitisation : Not classified Germ cell mutagenicity May cause genetic defects. Carcinogenicity : May cause cancer. Reproductive toxicity : Not classified : Not classified STOT-single exposure heptane (142-82-5) STOT-single exposure Not available methylcyclohexane (108-87-2) STOT-single exposure Not available octane (111-65-9) STOT-single exposure Not available toluene (108-88-3) STOT-single exposure Not available STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure. nonane (111-84-2) NOAEL (oral, rat, 90 days) 100 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents) NOAEC (inhalation, rat, vapour, 90 days) 24.3 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study) NOAEL (subchronic, oral, animal/male, 90 days) 100 mg/kg bodyweight Animal: mouse, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents) STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. Naphtha (petroleum), hydrodesulfurized heavy / Naphtha (petroleum), hydrodesulfurized heavy (64742-82-1) STOT-repeated exposure Causes damage to organs through prolonged or repeated exposure. Kerosine (petroleum) (8008-20-6) NOAEL (oral, rat, 90 days) 750 mg/kg bodyweight Animal: rat, Animal sex: female ≥ 0.024 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: NOAEC (inhalation, rat, vapour, 90 days) 28-Day Study) octane (111-65-9) NOAEC (inhalation, rat, vapour, 90 days) 24.3 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study) toluene (108-88-3) STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure. Aspiration hazard • Not classified nonane (111-84-2) False Animal studies and expert judgment for classification

## Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

Undecane (1120-21-4)		
Animal studies and expert judgment for classification	False	
Decane (124-18-5)		
Animal studies and expert judgment for classification	False	
Naphtha (petroleum), hydrodesulfurized heavy / Naphtha (petroleum), hydrodesulfurized heavy (64742-82-1)		
Animal studies and expert judgment for classification	False	
Kerosine (petroleum) (8008-20-6)		
Animal studies and expert judgment for classification	False	
heptane (142-82-5)		
Animal studies and expert judgment for classification	False	
methylcyclohexane (108-87-2)		
Animal studies and expert judgment for classification	False	
octane (111-65-9)		
Animal studies and expert judgment for classification	False	
toluene (108-88-3)		
Animal studies and expert judgment for classification	False	
xylene (1330-20-7)		
Animal studies and expert judgment for classification	False	

## SECTION 12: Ecological information

12.1. Toxicity	
Hazardous to the aquatic environment, short-term : (acute)	Toxic to aquatic life. Harmful to aquatic life with long lasting effects. Not classified. Not classified.
nonane (111-84-2)	
EC50 - Crustacea [1]	0.2 mg/l Test organisms (species): Daphnia magna
LOEC (chronic)	0.32 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0.17 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
heptane (142-82-5)	
BCF - Other aquatic organisms [1]	552 (BCFBAF v3.00, Calculated value)
Partition coefficient n-octanol/water (Log Pow)	4.66 (Experimental value)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.38 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
octane (111-65-9)	
EC50 - Crustacea [1]	0.3 mg/l Test organisms (species): Daphnia magna
LOEC (chronic)	0.32 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0.17 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

## Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

12.2. Persistence and degradability		
Miraplate liquid		
Persistence and degradability	No additional information available	
heptane (142-82-5)		
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.	
Biochemical oxygen demand (BOD)	1.92 g O <sub>2</sub> /g substance	
Chemical oxygen demand (COD)	0.06 g O <sub>2</sub> /g substance	
ThOD	3.52 g O <sub>2</sub> /g substance	
BOD (% of ThOD)	> 0.5 (5 day(s), Literature study)	

#### **12.3. Bioaccumulative potential**

Miraplate liquid		
Bioaccumulative potential	ive potential No additional information available	
heptane (142-82-5)		
BCF - Other aquatic organisms [1]	552 (BCFBAF v3.00, Calculated value)	
Partition coefficient n-octanol/water (Log Pow)	4.66 (Experimental value)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.38 (log Koc, SRC PCKOCWIN v2.0, Calculated value)	
Bioaccumulative potential	Potential for bioaccumulation ( $4 \ge Log$ Kow $\le 5$ ).	

### 12.4. Mobility in soil

Miraplate liquid		
Mobility in soil	No additional information available	
heptane (142-82-5)		
Surface tension	19.66 mN/m (25 °C)	
Partition coefficient n-octanol/water (Log Pow)	4.66 (Experimental value)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.38 (log Koc, SRC PCKOCWIN v2.0, Calculated value)	
Ecology - soil	Low potential for adsorption in soil.	
12.5. Other adverse effects		
Dzone :	Not classified	

Other adverse effects

: Not classified : No additional information available

SECTION 13: Disposal considerations	
13.1. Disposal methods	
Waste treatment methods Additional information	<ul><li>Dispose of contents/container in accordance with licensed collector's sorting instructions.</li><li>Flammable vapours may accumulate in the container.</li></ul>

### SECTION 14: Transport information

In accordance with SANS / IMDG / IATA

## Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

SANS	IMDG	ΙΑΤΑ	
14.1. UN number		L	
3295	3295	3295	
14.2. Proper Shipping Name		1	
HYDROCARBONS, LIQUID, N.O.S.	HYDROCARBONS, LIQUID, N.O.S.	Hydrocarbons, liquid, n.o.s.	
14.3. Transport hazard class(es)			
3	3	3	
14.4. Packing group		•	
III		III	
14.5. Environmental hazards		I	
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	
No supplementary information available			
14.6. Special precautions for user			
SANS			
Special provisions (SANS)	: 223		
imited quantities (SANS)	: 5 L		
imited quantities (SANS)	: 5L		
Packagings, large packagings and IBCs Packing nstructions (SANS)	: P001, IBC03, LP01		
Portable tank and bulk containers instructions SANS)	: T4		
Portable tank and bulk container special provisions SANS)	: TP1, TP29		
MDG			
Special provisions (IMDG)	: 223		
Packing instructions (IMDG)	: P001, LP01		
BC packing instructions (IMDG)	: IBC03		
ank instructions (IMDG)	: T4		
Fank special provisions (IMDG)	: TP1, TP29		
EmS-No. (Fire)	: F-E - FIRE SCHEDULE Echo - NON-WATE		
mS-No. (Spillage)	: S-D - SPILLAGE SCHEDULE Delta - FLAN	/MABLE LIQUIDS	
Stowage category (IMDG)	: A		
Properties and observations (IMDG)	: Immiscible with water.		
ATA			
PCA Excepted quantities (IATA)	: E1		
CA Limited quantities (IATA)	: Y344		
CA limited quantity max net quantity (IATA)	: 10L		
PCA packing instructions (IATA)	: 355		
PCA max net quantity (IATA)	: 60L		
CAO packing instructions (IATA)	: 366		
AO max net quantity (IATA)	: 220L		
Special provisions (IATA)	: A3, A224		
RG code (IATA)	: 3L		
4.7. Transport in bulk according to Annex	II of MARPOL 73/78 and the IBC Code		

#### Not applicable

### Safety Data Sheet

according to SANS 10234:2019 and SANS 11014:2010

#### **SECTION 15: Regulatory information**

15.1. Safety, health, and environmental national regulations specific for the product

No additional information available

#### SECTION 16: Other information

Issue date Revision date : 06/05/2024 : 06/05/2026

Full text of	H-statements
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H227	Combustible liquid
H303	May be harmful if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H313	May be harmful in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness
H340	May cause genetic defects
H350	May cause cancer
H372	Causes damage to organs through prolonged or repeated exposure
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects

Safety Data Sheet (SDS), South Africa

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.